



Chamäleon GmbH  
Rudolf-Diesel-Straße, 8a  
69115 Heidelberg-Germany  
Tel.: +49-(0)-6221 520440  
Fax: +49-(0)-6221 520449  
E-mail: info@chamaeleon-produktion.de  
http: //www.chamaeleon-produktion.de

***SAFETY DATA SHEET***  
*according to 1907/2006/EC, Article 31    Revision date: 29.01.2020*

**1- IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING**

**Product details**

**Trade name:** Hardener Slow

**Article number:** 12284, 12287

**Relevant identified uses of the substance or mixture and uses advised against:**

No further relevant information available.

**Intended use:** Car refinishing Product/ Hardening agent/ Curing agent

**Manufacturer/Supplier:** Chamäleon GmbH

Rudolf-Diesel-Straße, 8a, 69115 Heidelberg -- Germany

**Further information obtainable from:** Product Safety Department

**Information in case of emergency:** + 49 70024112112 (CH)

**2 – HAZARDS IDENTIFICATION**

**Classification of the substance or mixture**

**Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

**Label elements**

**Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

**Hazard pictograms**



GHS02

GHS07



Chamäleon GmbH  
Rudolf-Diesel-Straße, 8a  
69115 Heidelberg-Germany  
Tel.: +49-(0)-6221 520440  
Fax: +49-(0)-6221 520449  
E-mail: info@chamaeleon-produktion.de  
http: //www.chamaeleon-produktion.de

**Signal word** Warning

**Hazard-determining components of labelling:**

Hexamethylene diisocyanate, oligomers

2-Butoxyethyl acetate

2-Methoxy-1-methylethyl acetate

n-Butyl acetate

**Hazard statements**

H226 Flammable liquid and vapour.

H332 Harmful if inhaled.

H317 May cause an allergic skin reaction.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

**Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.

**Additional information:**

EUH204 Contains isocyanates. May produce an allergic reaction.

Restricted to professional users.

**Other hazards**

**Results of PBT and vPvB assessment**

**PBT:** Not applicable.

**vPvB:** Not applicable.

**3- COMPOSITION/INFORMATION ON INGREDIENTS**

**Chemical characterization: Mixtures**

**Description:** Mixture of substances listed below with nonhazardous additions.

| <b>Dangerous components:</b>                                    |  |         |
|---|--|---------|
| CAS: 28182-81-2<br>NLP: 500-060-2<br>Reg.nr.: 01-2119485796-17  | Hexamethylene diisocyanate, oligomers<br>Acute Tox. 4, H332; Skin Sens. 1, H317; STOT SE 3, H335 | 50-100% |
| CAS: 112-07-2<br>EINECS: 203-933-3<br>Reg.nr.: 01-2119475112-47 | 2-Butoxyethyl acetate<br>Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332              | 10-25%  |
| CAS: 108-65-6<br>EINECS: 203-603-9<br>Reg.nr.: 01-2119475791-29 | 2-Methoxy-1-methylethyl acetate<br>Flam. Liq. 3, H226; STOT SE 3, H336                           | 10-25%  |
| CAS: 123-86-4   | n-Butyl acetate  | 5-<10%  |



Chamäleon GmbH  
 Rudolf-Diesel-Straße, 8a  
 69115 Heidelberg-Germany  
 Tel.: +49-(0)-6221 520440  
 Fax: +49-(0)-6221 520449  
 E-mail: info@chamaeleon-produktion.de  
 http: //www.chamaeleon-produktion.de

|   |   |            |
|---|---|------------|
| EINECS: 204-658-1<br>Reg.nr.: 01-2119485493-29                  | Flam. Liq. 3, H226; STOT SE 3, H336   |            |
| CAS: 822-06-0<br>EINECS: 212-485-8<br>Reg.nr.: 01-2119457571-37 | hexamethylene-di-isocyanate   | ≥0.1-<0.5% |
|   | Acute Tox. 2, H330; Resp. Sens. 1, H334; Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335 |            |

**Additional information:** For the wording of the listed risk phrases refer to section 16.

#### 4- FIRST - AID MEASURE

##### **Description of first aid measures**

##### **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

In case of irregular breathing or respiratory arrest provide artificial respiration.

##### **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

**After skin contact:** Generally the product does not irritate the skin.

**After eye contact:** Rinse opened eye for several minutes under running water.

**After swallowing:** If symptoms persist consult doctor.

##### **Indication of any immediate medical attention and special treatment needed**

No further relevant information available

##### **Information for doctor:**

#### 5- FIRE - FIGHTING MEASURE

##### **Extinguishing media**

**Suitable extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.

**For safety reasons unsuitable extinguishing agents:** Water with full jet

##### **Special hazards arising from the substance or mixture**

In case of fire, the following can be released:

Nitrogen oxides (NO<sub>x</sub>)

Carbon monoxide (CO)

Hydrogen cyanide (HCN)

##### **Advice for firefighters**

**Protective equipment:** Mouth respiratory protective device.



Chamäleon GmbH  
Rudolf-Diesel-Straße, 8a  
69115 Heidelberg-Germany  
Tel.: +49-(0)-6221 520440  
Fax: +49-(0)-6221 520449  
E-mail: info@chamaeleon-produktion.de  
http: //www.chamaeleon-produktion.de

## **6– ACCIDENTAL RELEASE MEASURE**

### **Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

**Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

### **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

Contain and collect spillages with non-combustible absorbent materials (e.g. sand, earth, diatomaceous earth) and place in a suitable container.

Decontaminate immediately with suitable mixture (flammable):

- as such usable (inflammatory!):

water 45 Vol.%

ethanol or isopropanol 50 Vol.%

ammonia solution (Density= 0.88) 5 Vol.%

- alternatively (non-flammable):

sodium carbonate 5 Vol.%

water 95 Vol.%

Add the same decontaminant to any residues and allow to stand for several days in a non-sealed container until no further reaction occurs. Once this stage is reached, close the container and dispose of in accordance with the waste regulations (see Section 13).

### **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## **7– HANDLING AND STORAGE**

### **Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Persons with a history of asthma, allergies or chronic or recurrent respiratory diseases should only be employed in processes in which this product is used under appropriate medical supervision.

### **Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

### **Conditions for safe storage, including any incompatibilities**

#### **Storage:**

**Requirements to be met by storerooms and receptacles:** No special requirements.

#### **Information about storage in one common storage facility:**

Do not store together with reducing agents, heavy-metal compounds, acids and alkalis.

Store away from foodstuffs.

#### **Further information about storage conditions:**

Keep container tightly sealed.



Chamäleon GmbH  
 Rudolf-Diesel-Straße, 8a  
 69115 Heidelberg-Germany  
 Tel.: +49-(0)-6221 520440  
 Fax: +49-(0)-6221 520449  
 E-mail: info@chamaeleon-produktion.de  
 http: //www.chamaeleon-produktion.de

Store separately from oxidising agents, strongly alkaline and strongly acidic materials, amines, alcohol and water.

**Storage class:** 3

**Specific end use(s)** No further relevant information available.

## **8 – EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Additional information about design of technical facilities:** No further data; see item 7.

### **Control parameters**

| <b>Ingredients with limit values that require monitoring at the workplace:</b> |  |
|--|--|
| 28182-81-2 Hexamethylene diisocyanate, oligomers                               |  |
| EBW  | Short-term value: 0.5 mg/m <sup>3</sup><br>exposition evaluation valu TRGS 430 (EBW)                       |
| 112-07-2 2-Butoxyethyl acetate   |  |
| WEL  | Short-term value: 332 mg/m <sup>3</sup> , 50 ppm<br>Long-term value: 133 mg/m <sup>3</sup> , 20 ppm<br>Sk  |
| 108-65-6 2-Methoxy-1-methylethyl acetate                                       |  |
| WEL  | Short-term value: 548 mg/m <sup>3</sup> , 100 ppm<br>Long-term value: 274 mg/m <sup>3</sup> , 50 ppm<br>Sk |
| 123-86-4 n-Butyl acetate   |  |
| WEL  | Short-term value: 966 mg/m <sup>3</sup> , 200 ppm<br>Long-term value: 724 mg/m <sup>3</sup> , 150 ppm      |
| 822-06-0 hexamethylene-di-isocyanate   |  |
| WEL  | Short-term value: 0.07 mg/m <sup>3</sup><br>Long-term value: 0.02 mg/m <sup>3</sup><br>Sen; as -NCO        |

| <b>Ingredients with biological limit values:</b> |  |
|--|--|
| 822-06-0 hexamethylene-di-isocyanate             |  |
| BMGV   | 1 µmol creatinine/mol<br>Medium: urine<br>Sampling time: At the end of the period od exposure<br>Parameter: isocyanate-derived diamine |

**Additional information:** The lists valid during the making were used as basis.

### **Exposure controls**

#### **Personal protective equipment:**

All personal protective equipment, including respiratory protective equipment, used to control exposure to hazardous substances must be selected to meet the requirements of the COSHH Regulations.

#### **General protective and hygienic measures:**



Chamäleon GmbH  
Rudolf-Diesel-Straße, 8a  
69115 Heidelberg-Germany  
Tel.: +49-(0)-6221 520440  
Fax: +49-(0)-6221 520449  
E-mail: info@chamaeleon-produktion.de  
http: //www.chamaeleon-produktion.de

Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.  
Do not inhale gases / fumes / aerosols.

**Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A/P2 (EN 141, EN 143)

**Protection of hands:**

Protective gloves (EN 374)

**Material of gloves**

Butyl rubber, BR

Recommended thickness of the material:  $\geq 0.7$  mm.

**Penetration time of glove material** Value for the permeation: Level  $\leq 2$

**Eye protection:** Tightly sealed goggles

**9 – PHYSICAL AND CHEMICAL PROPERTIES**

| <b>Information on basic physical and chemical properties</b> |  |
|--|--|
| <b>General Information</b>                                   |  |
| <b>Appearance:</b>   |  |
| Form:  | Fluid  |
| Colour:  | According to product specification   |
| Odour:   | Characteristic   |
| Odour threshold:   | Not determined.  |
| pH-value:  | Not determined.  |
| <b>Change in condition</b>                                   |  |
| Melting point/freezing point:                                | Undetermined.  |
| Initial boiling point and boiling range:                     | 124-128 °C   |
| Flash point:   | 30 °C (DIN 53213)  |
| Flammability (solid, gas):                                   | Not applicable.  |
| Ignition temperature:  | 280 °C (DIN 51794)   |
| Decomposition temperature:                                   | Not determined.  |
| Auto-ignition temperature::                                  | Product is not selfigniting.   |
| Danger of explosion:   | Product is not explosive. However, formation of explosive air/vapour mixtures are possible.. |
| <b>Explosion limits:</b>                                     |  |
| Lower:   | 1.5 Vol %  |
| Upper:   | 10.8 Vol %   |
| Vapour pressure at 20 °C:                                    | 10.7 hPa   |



Chamäleon GmbH  
Rudolf-Diesel-Straße, 8a  
69115 Heidelberg-Germany  
Tel.: +49-(0)-6221 520440  
Fax: +49-(0)-6221 520449  
E-mail: info@chamaeleon-produktion.de  
http: //www.chamaeleon-produktion.de

|  |  |
|--|--|
| <b>Density at 20 °C:</b>   | 1.05 g/cm <sup>3</sup> (DIN 53217)         |
| <b>Relative density</b>  | Not determined.                            |
| <b>Vapour density</b>  | Not determined.                            |
| <b>Evaporation rate</b>  | Not determined.                            |
| <b>Solubility in / Miscibility with water:</b> Not miscible or difficult to mix. |  |
| <b>Partition coefficient: n-octanol/water:</b> Not determined.                   |  |
| <b>Viscosity:</b>  |  |
| <b>Dynamic:</b>  | Not determined.                            |
| <b>Kinematic at 20 °C:</b>   | 18 s (DIN 53211/4)                         |
| <b>Solvent content:</b>  |  |
| <b>VOC (EC)</b>  | 45.89 %                                    |
| <b>Solids content (weight-%):</b>  | 54.1 %                                     |
| <b>Other information</b>   | No further relevant information available. |

## 10– STABILITY AND REACTIVITY

**Reactivity** No further relevant information available.

**Chemical stability**

**Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

**Possibility of hazardous reactions** No dangerous reactions known.

**Conditions to avoid** No further relevant information available.

**Incompatible materials:** No further relevant information available.

**Hazardous decomposition products:**

Possible in traces.

Nitrogen oxides

Hydrogen chloride (HCl)

Hydrogen cyanide (prussic acid)

Carbon monoxide

Nitrogen oxides (NO<sub>x</sub>)

## 11– TOXICOLOGICAL INFORMATION

**Information on toxicological effects**

**Acute toxicity:**

Harmful if inhaled.

**LD/LC50 values relevant for classification:**

112-07-2 2-Butoxyethyl acetate

|        |      |                      |
|--------|------|----------------------|
| Oral   | LD50 | 1,880 mg/kg (rat)    |
| Dermal | LD50 | 1,480 mg/kg (rabbit) |

**Primary irritant effect:**



Chamäleon GmbH  
Rudolf-Diesel-Straße, 8a  
69115 Heidelberg-Germany  
Tel.: +49-(0)-6221 520440  
Fax: +49-(0)-6221 520449  
E-mail: info@chamaeleon-produktion.de  
http: //www.chamaeleon-produktion.de

**Skin corrosion/irritation** Based on available data, the classification criteria are not met.  
**Serious eye damage/irritation** Based on available data, the classification criteria are not met.  
**Respiratory or skin sensitisation**  
May cause an allergic skin reaction.  
**CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**  
**Germ cell mutagenicity** Based on available data, the classification criteria are not met.  
**Carcinogenicity** Based on available data, the classification criteria are not met.  
**Reproductive toxicity** Based on available data, the classification criteria are not met.  
**STOT-single exposure**  
May cause respiratory irritation. May cause drowsiness or dizziness.  
**STOT-repeated exposure** Based on available data, the classification criteria are not met.  
**Aspiration hazard** Based on available data, the

## 12 – ECOLOGICAL INFORMATION

### **Toxicity**

**Aquatic toxicity:** No further relevant information available.

**Persistence and degradability** No further relevant information available.

**Bioaccumulative potential** No further relevant information available.

**Mobility in soil** No further relevant information available.

### **Additional ecological information:**

#### **General notes:**

**Water hazard class 1 (German Regulation) :** slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

#### **Results of PBT and vPvB assessment**

**PBT:** Not applicable.

**vPvB:** Not applicable.

**Other adverse effects** No further relevant information available.

## 13– DISPOSAL CONSIDERATION

### **Waste treatment methods**

#### **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

| <b>European waste catalogue</b> |   |
|---------------------------------|---|
| 08 01 11*                       | waste paint and varnish containing organic solvents or other dangerous substances |

#### **Uncleaned packaging:**

**Recommendation:** Disposal must be made according to official regulations.





Chamäleon GmbH  
Rudolf-Diesel-Straße, 8a  
69115 Heidelberg-Germany  
Tel.: +49-(0)-6221 520440  
Fax: +49-(0)-6221 520449  
E-mail: info@chamaeleon-produktion.de  
http: //www.chamaeleon-produktion.de

## 14- TRANSPORT INFORMATION

### UN-Number

ADR, IMDG, IATA UN1263

### UN proper shipping name

ADR UN1263 PAINT RELATED MATERIAL  
IMDG, IATA PAINT RELATED MATERIAL

### Transport hazard class(es)

ADR



Class 3 (F1) Flammable liquids.  
Label 3

IMDG, IATA



Class 3 Flammable liquids.  
Label 3

### Packing group

ADR, IMDG, IATA III

### Environmental hazards:

Marine pollutant: No

### Special precautions for user

Warning: Flammable liquids.  
Danger code (Kemler): 30  
EMS Number: F-E,S-E  
Stowage Category: A

### Transport in bulk according to Annex II of

Marpol and the IBC Code Not applicable.

### Transport/Additional information:

ADR

Transport category 3  
Tunnel restriction code D/E



Chamäleon GmbH  
Rudolf-Diesel-Straße, 8a  
69115 Heidelberg-Germany  
Tel.: +49-(0)-6221 520440  
Fax: +49-(0)-6221 520449  
E-mail: info@chamaeleon-produktion.de  
http: //www.chamaeleon-produktion.de

## IMDG

Limited quantities (LQ) 5L

UN "Model Regulation": UN 1263 PAINT RELATED MATERIAL, 3, III

## 15 – REGULATORY INFORMATION

**Safety, health and environmental regulations/legislation specific for the substance or mixture.**

**Directive 2012/18/EU**

**Named dangerous substances - ANNEX I** None of the ingredients is listed.

**Seveso category** P5c FLAMMABLE LIQUIDS

**Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000

**Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t

**REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction:** 3

**National regulations:**

| Class | Share in % |
|-------|------------|
| I     | <1         |
| NK    | 25-50      |

**Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16-OTHER INFORMATION

### **Relevant phrases**

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H330 Fatal if inhaled.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

### **Classification according to Regulation (EC) No 1272/2008**

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

### **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)



Chamäleon GmbH  
Rudolf-Diesel-Straße, 8a  
69115 Heidelberg-Germany  
Tel.: +49-(0)-6221 520440  
Fax: +49-(0)-6221 520449  
E-mail: [info@chamaeleon-produktion.de](mailto:info@chamaeleon-produktion.de)  
<http://www.chamaeleon-produktion.de>

IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
VOC: Volatile Organic Compounds (USA, EU)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative  
Flam. Liq. 3: Flammable liquids – Category 3  
Acute Tox. 2: Acute toxicity – Category 2  
Acute Tox. 4: Acute toxicity – Category 4  
Skin Irrit. 2: Skin corrosion/irritation – Category 2  
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2  
Resp. Sens. 1: Respiratory sensitisation – Category 1  
Skin Sens. 1: Skin sensitisation – Category 1  
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

The information contained in these sheets is based on the present state of knowledge and current national legislation. It provides guidance on health, safety and environmental aspects and should not be construed as any guarantee of technical performance or suitability for particular applications.



Chamäleon GmbH  
Rudolf-Diesel-Straße, 8a  
69115 Heidelberg-Germany  
Tel.: +49-(0)-6221 520440  
Fax: +49-(0)-6221 520449  
E-mail: [info@chamaeleon/produktion.de](mailto:info@chamaeleon/produktion.de)  
<http://www.chamaeleon/produktion.de>