

**TECHNICAL DATA SHEET**

Revision date: 10.06.2023

**PRE-FILL STANDARD**

<b>Article number:</b>	<b>25001</b>
<b>Colour:</b>	depending on filling
<b>Intended use:</b>	Car refinishing product/ Preparation
<b>General characteristics:</b>	<p>Chamäleon Pre-fill standard is a pre-filled can with propellant gases and solvent (275 ml) that can be filled with solvent-based basecoats (max. 100 ml). Ideal for spot repair or refinishing parts.</p> <p>A spray can pre-filled with propellant and solvents. The paint is transferred via a filling device into the can to produce a ready-to-use end product (dealers liability)</p> <ul style="list-style-type: none"><li>▪ simple, time-saving application</li><li>▪ excellent atomisation</li><li>▪ light blending</li></ul>

**Physical characteristics:****Smell:** solvent**Efficiency:** depending on consistence and colour of the ground**Substrate:** depending on the colour of the substrate applicable on Primer filler, 2K Primer filler, 1K Epoxy primer, cured paint sanded**Drying time at 20°C, 50% relative air humidity:** drying time depends on surrounding temperature, air humidity, thickness of the applied coat and the filled type of paint (refer to information of the paint manufacturer)**Size:** aerosol cans, maximum nominal volume 400 ml.**VOC-value:** 218g**Processing conditions:**

Please only use in an adequate ventilated environment with an ample supply of fresh air. Processing temperature should be at least +10 °C and max. air humidity should not exceed 80%.



CHAMÄLEON GMBH / RUDOLF-DIESEL-STRASSE 8A / 69115 HEIDELBERG / GERMANY

CHAMÄLEON GMBH  
RUDOLF-DIESEL-STRASSE 8A  
69115 HEIDELBERG  
GERMANY

FON 0049 (0) 6221 - 520 440  
FAX 0049 (0) 6221 - 520 449  
MAIL INFO@CHAMAELEON-PRODUKTION.DE  
WEB WWW.CHAMAELEON-PRODUKTION.DE

## Application process:

Before use, carefully read and observe the warning texts on the label!

- Clean the surface to be painted thoroughly with Chamäleon Silicone remover, then sand
- Larger bare surfaces must be pre-primed with the appropriate Chamäleon primer
- The area must be dry and free of dust and grease
- Shake the can vigorously for 2 minutes
- Carry out spray test
- Compatibility testing is necessary

### For professional use only

**Wear an appropriate respirator (recommended type A2/P3).**

## Storage stability:

Empty cans: 5 years.

Filled cans: depending on type of paint from several hours up to 6 months (information from a specialist dealer). If appropriate storage provided (=10°-25°C, relative air humidity max. 60%)

This release replaces all eventually earlier issued versions.

For additional information, not contained in this technical data sheet, please contact the supplier under:

e-mail: [info@chamaeleon-produktion.de](mailto:info@chamaeleon-produktion.de)

For safety information, please refer to the corresponding safety data sheet.

STEUERNUMMER/TAX NR.: DE 231468544  
EORI NR./CUSTOMS NR.: DE 6029442 / HRB 9778  
GESCHÄFTSFÜHRER/CEO: SASCHA HAGEMANN

BANK HEIDELBERGER VOLKSBANK EG  
IBAN DE78 6729 0000 0042 8627 03  
BIC GENODE61HDI