

**TECHNICAL DATA SHEET***Revision date: 08.09.2020***ANTI SILICONE ADDITIVE****Article number:** **13611****Intended use:** Car refinishing product/ Paint additive  
**General characteristics:** Anti Silicone Additive avoids Fish eyes and improves the flow when coating surfaces with residues of silicone, polish, wax and grease. Suitable for Chamäleon 2K paints and paints based on synthetic resins.**Quantity to add:**  
2 up to max. 5 % Anti Silicone Additive to base paint or to base paint after addition of hardener in case of 2K paint materials.**Painting process:****Colour:** colourless**Hardener:** -**Mixing ratio:** -**Dilution:** -**Spraying viscosity 4 mm DIN:** Gravity spray gun X - X s**Processing conditions:**Please only use in an adequate ventilated environment with an ample supply of fresh air.  
Processing temperature should be at least +10 °C and max. air humidity should not exceed 80%.**Processing tips**

The use of Anti Silicone Additive has no impact on drying times.

**VOC regulation:**

-

This release replaces all eventually earlier issued versions.

For additional information, not contained in this technical data sheet, please contact the supplier under:

e-mail: [info@chamaeleon-produktion.de](mailto:info@chamaeleon-produktion.de)

For safety information, please refer to the corresponding safety data sheet.