

CHAMÄLEON GMBH / RUDOLF-DIESEL-STRASSE 8A / 69115 HEIDELBERG / GERMANY

CHAMÄLEON GMBH RUDOLF-DIESEL-STRASSE 8A 69115 HEIDELBERG GERMANY

FON 0049 (0) 6221 - 520 440 FAX 0049 (0) 6221 - 520 449

MAIL INFO@CHAMAELEON-PRODUKTION.DE WEB WWW.CHAMAELEON-PRODUKTION.DE

TECHNICAL DATA SHEET

POLISHING PAD - SOFT (Dark Grey)

Article number: 49100, 49200, 49300, 49400

Intended use: Car refinishing product/ Polishing, griding

General characteristics:

for mechanical polishing and griding;

suited for using with coarse-grained polishing pastes.

Product characteristics:

- structure of the foam allow to hold the water inside the pad, what decrease the temperature of the polishing surface;
- the pad does not get into vibration during the work, which has a considerble effect on its life time;
- the Velcro holder is made from very strong, reusable material. It allows the pad to be securaly fitted into the polisher;
- the plastic holder is topped with the nut what easily and permanently allow to install and uninstall the pad on the polisher/sander;
- color: Black (dark grey)

Available types of working surface:

- flat
- waffle

Technical characteristics:

- the plastic holder is manufactured of hard poli(akrylonitryl-co-butadien-co-styren) (ABS) plastic,
- the Velcro holder hook-up type
- the foam is polyurethane, polyester type, high resistantce and shock absorption
- genera physical parameters of foam:

FEATURES	UNIT	VALUE
Density	kg/m3	19.5 – 22.5





CHAMÄLEON GMBH RUDOLF-DIESEL-STRASSE 8A 69115 HEIDELBERG GERMANY

FON 0049 (0) 6221 - 520 440
FAX 0049 (0) 6221 - 520 449
MAIL INFO@CHAMAELEON-PRODUKTION.DE
WEB WWW.CHAMAELEON-PRODUKTION.DE

Rigidity 40%	kPa	2.3 - 3.8
Elongation at break	%	160
Tensile strenght	kPa	110
Cell diameter	Mikron	440 – 520
Max compression set	%	5

Usage:

the pad can be applied both wet and dry at maximum rotation speed 2600 rpm without load.

Available sizes: Available holders:

150mm x 50mm 150mm x 25mm plastic thread M14 Velcro

This release replaces all eventually earlier issued versions.

For additional information, not contained in this Technical Data Sheet, please contact the supplier via: info@chamaeleon-produktion.de

For safety information, please refer to the corresponding Safety Data Sheet.