





CHAMÄLEON GMBH / RUDOLF-DIESEL-STRASSE 8A / 69115 HEIDELBERG / GERMANY

CHAMÄLEON GMBH RUDOLF-DIESEL-STRASSE 8A 69115 HEIDELBERG GERMANY

FON 0049 (0) 6221 - 520 440 FAX 0049 (0) 6221 - 520 449 MAIL INFO®CHAMAELEON-PRODUKTION.DE WEB WWW.CHAMAELEON-PRODUKTION.DE

TECHNICAL DATA SHEET

Revision date: 10.08.2023

SPOT BLENDER

Article number:

Colour:

Intended use:

General characteristics:

Transparent

26504

Car refinishing product/ Preparation

Chamäleon Spot blender blends the transition between the old and the new lacquer layer in case of spot repairs. The blending properties of the spray enable a smooth blend between new and old paint to be achieved. Spot blender has a fine and precise jet-spray which enables an instant and invisible result

As a result of the blending of the overspray, a smooth transition is obtained between the old and the new lacquer.

- Instant (in)visible result
- Directed jetspray
- Fine spray

Physical and chemical characteristics:

Base: organic solvents Smell: characteristic Degree of gloss: gloss, >75 GU Vapour pressure: 4000/20 bar

Application process:

Before use, carefully read and observe the warning texts on the label!

- The aerosol should have room temperature. Best processing temperature 10 to 25°C.
- Before use, shake the aerosol.
- The spot blender can be applied when the lacquer is tack free.
- Spray the surface with spot blender till the overspray blends like a film.
- The drying time depends on the ambient temperature and the humidity of the air.

BANK HEIDELBERGER VOLKSBANK EG IBAN DE78 6729 0000 0042 8627 03 BIC GENODE61HD1





CHAMÄLEON GMBH / RUDOLF-DIESEL-STRASSE 8A / 69115 HEIDELBERG / GERMANY

CHAMÄLEON GMBH RUDOLF-DIESEL-STRASSE 8A 69115 HEIDELBERG GERMANY

 FON
 0049 (0) 6221 - 520 440

 FAX
 0049 (0) 6221 - 520 449

 MAIL
 INFO@CHAMAELEON-PRODUKTION.DE

 WEB
 WWW.CHAMAELEON-PRODUKTION.DE

Processing conditions:

Please only use in an adequate ventilated environment with an ample supply of fresh air. Processing temperature should be at least +10 °C and max. air humidity should not exceed 80%.

Storage stability:

10 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)

This release replaces all eventually earlier issued versions.

For additional information, not contained in this technical data sheet, please contact the supplier under: e-mail: info@chamaeleon-produktion.de For safety information, please refer to the corresponding Safety data sheet.

STEUERNUMMER/TAX NR.: DE 231468544 EORI NR./CUSTOMS NR.: DE 6029442 / HRB 9778 GESCHÄFTSFÜHRER/CEO: SASCHA HAGEMANN BANK HEIDELBERGER VOLKSBANK EG IBAN DE78 6729 0000 0042 8627 03 BIC GENODE61HD1