

**TECHNICAL DATA SHEET***Revision date: 10.04.2025***AEROSOL HOLLOW SECTION WAX**

<b>Article number:</b>	<b>26740</b>
<b>Colour:</b>	white-transparent
<b>Intended use:</b>	Car refinishing Product/ Anticorrosion additive
<b>General characteristics:</b>	<p>High quality preservative to treat the hollow spaces in vehicle bodywork.</p> <ul style="list-style-type: none"><li>▪ excellent corrosion prevention</li><li>▪ resistant to weather influences</li><li>▪ resistant to weak acids and bases</li><li>▪ good penetrating properties</li></ul>

**TECHNICAL CHARACTERISTICS****Base:** wax**Smell:** characteristic**Consumption:** 1.0 - 1.5m<sup>2</sup> (500 ml)**APPLICATION PROCESS**

Before use, carefully read and observe the warning texts on the label!

**Processing conditions:**

Please only use in an adequate ventilated environment with an ample supply of fresh air. Processing temperature should be from +12 °C to +25 °C and max. air humidity should not exceed 80%.

**Processing tips:**

- Wear a respirator (type A2/P3 is recommended)
- The aerosol should have room temperature
- Before use, test the compatibility of the surface
- Before use, shake the aerosol for 2 min
- Apply the wax generously in the hollow areas using the adapter
- Clean the valve after use (turn aerosol upside down and press the nozzle for approximately 5 sec)

### **VOC regulation:**

EU limit value: Category B/e 840 g/l

This product contains max 570.8 g/l VOC

### **Shelf life:**

120 months, if stored in tightly closed original containers.

This release replaces all eventually earlier issued versions.

For additional information, not contained in this Technical Data Sheet, please contact the supplier under:

e-mail: [info@chamaeleon-produktion.de](mailto:info@chamaeleon-produktion.de)

For safety information, please refer to the corresponding Safety Data Sheet.