

SAFETY DATA SHEET
according to UK REACH

Revision date: 04.08.2025

**1- IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/
UNDERTAKING****Product details****Trade name:** Wet on wet primer**Article number:** 14671**Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.

Intended use: Car refinishing Product/ Filler**Manufacturer/Supplier:**

Chamäleon GmbH

Rudolf-Diesel-Straße, 8a, 69115 Heidelberg

Germany

Further information obtainable from: Product Safety Department**Information in case of emergency:** + 49 70024112112 (CH)**2 – HAZARDS IDENTIFICATION****Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008**

GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



GHS02 GHS07 GHS09

Signal word Warning

Hazard-determining components of labelling:

Pentaerythritol tetrakis(3-mercaptopropionate)

Dibutyltin dilaurate

Hazard statements

H226 Flammable liquid and vapour.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P403+P235 Store in a well-ventilated place. Keep cool.

Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

3- COMPOSITION/INFORMATION ON INGREDIENTS

Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 123-86-4	n-Butyl acetate	<15%
EINECS: 204-658-1	Flam. Liq. 3, H226; STOT SE 3, H336, EUH066	
Reg.nr.: 01-2119485493-29		

CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	Xylene Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	5-<10%
CAS: 7779-90-0 EINECS: 231-944-3 Reg.nr.: 01-2119485044-40	Trizinc bis(orthophosphate) Aquatic Acute 1, H400; Aquatic Chronic 1, H410	2.5-<10%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29	2-Methoxy-1-methylethyl acetate Flam. Liq. 3, H226; STOT SE 3, H336	2.5-<10%
CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119489370-35	Ethylbenzene Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Aquatic Chronic 3, H412	<2.5%
CAS: 112-07-2 EINECS: 203-933-3 Reg.nr.: 01-2119475112-47	2-Butoxyethyl acetate Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332	1-<2.5%
CAS: 77-58-7 EINECS: 201-039-8 Reg.nr.: 01-2119496068-27	dibutyltin dilaurate Muta. 2, H341; Repr. 1B, H360FD; STOT SE 1, H370; STOT RE 1, H372; Skin Corr. 1C, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1, H317	≥0.25- <0.3%
CAS: 1314-13-2 EINECS: 215-222-5 Reg.nr.: 01-2119463881-32	zinc oxide Aquatic Acute 1, H400; Aquatic Chronic 1, H410	≥0.025- <0.25%
CAS: 7575-23-7 EINECS: 231-472-8 Reg.nr.: 01-2119486981-23	Pentaerythritol tetrakis(3-mercaptopropionate) Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410, (M=10); Acute Tox. 4, H302; Skin Sens. 1A, H317	≥0.1- <0.25%

Additional information:

For the wording of the listed hazard phrases refer to section 16.

4- FIRST - AID MEASURE

Description of first aid measures

General information: Immediately remove any clothing soiled by the product.

After inhalation: Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact: Immediately rinse with water.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: If symptoms persist consult doctor.

Most important symptoms and effects, both acute and delayed No further relevant information available. **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5- FIRE - FIGHTING MEASURE

Extinguishing media

Suitable extinguishing agents:

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents: Water with full jet

Special hazards arising from the substance or mixture: No further relevant information available.

Advice for firefighters

Protective equipment: No special measures required.

6- ACCIDENTAL RELEASE MEASURE

Personal precautions, protective equipment and emergency procedures:

Wear protective equipment. Keep unprotected persons away.

Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Reference to other sections:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7- HANDLING AND STORAGE

Precautions for safe handling:

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: No special requirements.

Information about storage in one common storage facility: Store away from foodstuffs.

Further information about storage conditions: Keep container tightly sealed.

Storage class: 3

Specific end use(s): No further relevant information available.

8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

Ingredients with limit values that require monitoring at the workplace:	
123-86-4 n-Butyl acetate	
WEL	Short-term value: 966 mg/m ³ , 200 ppm Long-term value: 724 mg/m ³ , 150 ppm
1330-20-7 Xylene	
WEL	Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV
108-65-6 2-Methoxy-1-methylethyl acetate	
WEL	Short-term value: 548 mg/m ³ , 100 ppm Long-term value: 274 mg/m ³ , 50 ppm Sk
100-41-4 Ethylbenzene	
WEL	Short-term value: 552 mg/m ³ , 125 ppm Long-term value: 441 mg/m ³ , 100 ppm Sk
112-07-2 2-Butoxyethyl acetate	
WEL	Short-term value: 332 mg/m ³ , 50 ppm Long-term value: 133 mg/m ³ , 20 ppm Sk

77-58-7 dibutyltin dilaurate		
WEL	Short-term value: 0.2 mg/m³ Long-term value: 0.1 mg/m³ as Sn; Sk	
DNELs		
123-86-4 n-Butyl acetate		
Dermal	DNEL	6 mg/kg (general population) 11 mg/kg (Arbeiter)
Inhalative	DNEL	300 mg/m³ (general population) 600 mg/m³ (Arbeiter)
1330-20-7 Xylene		
Dermal	DNEL	212 mg/kg (Arbeiter)
Inhalative	DNEL	221 mg/m³ (Arbeiter)
112-07-2 2-Butoxyethyl acetate		
Dermal	DNEL	169 mg/kg (Arbeiter)
Inhalative	DNEL	133 mg/m³ (Arbeiter)
Ingredients with biological limit values:		
1330-20-7 Xylene		
BMGV	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid	

Additional information: The lists valid during the making were used as basis.

Exposure controls

Appropriate engineering controls: No further data; see section 7.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection

Tightly sealed goggles

9 – PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

General Information

Physical state

Liquid

Colour:

According to product specification

Odour:

Characteristic

Odour threshold:

Not determined.

Melting point/freezing point:

Undetermined.

Boiling point or initial boiling point and boiling range:

124-128 °C (123-86-4 n-Butyl acetate)

Flammability:

Flammable.

Lower and upper explosion limit

Lower:

1.2 Vol % (123-86-4 n-Butyl acetate)

Upper:

8.5 Vol % (123-86-4 n-Butyl acetate)

Flash point:

24 °C (DIN EN ISO 1523:2002)

Auto-ignition temperature:

390 °C (DIN 51794, 123-86-4 n-Butyl acetate)

Decomposition temperature:

Not determined.

pH:

Not determined.

Viscosity:

Kinematic viscosity at 20 °C

>60 s (DIN 53211/4)

Dynamic:

Not determined.

Solubility

water:

Not miscible or difficult to mix.

Partition coefficient n-octanol/water (log value):

Not determined.

Vapour pressure at 20 °C:

10.7 hPa (123-86-4 n-Butyl acetate)

Vapour pressure at 50 °C:

55 hPa

Density and/or relative density

Density at 20 °C:

1.477 g/cm³ (DIN EN ISO 2811-1)

Relative density

Not determined.

Vapour density

Not determined.

Other information

Appearance:

Form:

Important information on protection of health and environment, and on safety.

Ignition temperature:

Explosive properties:

Solvent content:

VOC (EC)

Solids content (weight-%):

Change in condition

Evaporation rate:

Information with regard to physical hazard classes

Explosives:

Flammable gases:

Aerosols:

Oxidising gases:

Gases under pressure:

Flammable liquids:

Flammable solids:

Self-reactive substances and mixtures:

Pyrophoric liquids:

Pyrophoric solids:

Self-heating substances and mixtures:

Substances and mixtures, which emit flammable gases in contact with water:

Oxidising liquids:

Oxidising solids:

Organic peroxides:

Corrosive to metals:

Desensitised explosives:

Fluid

Product is not selfigniting.

Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

26.92 %

73.1 %

Not determined.

Void

Void

Void

Void

Void

Flammable liquid and vapour.

Void

Void

Void

Void

Void

Void

Void

Void

Void

Void

Void

10- STABILITY AND REACTIVITY

Reactivity No further relevant information available.

Chemical stability

Thermal decomposition / conditions to be avoided: No decomposition if used according to

specifications.

Possibility of hazardous reactions: No dangerous reactions known.

Conditions to avoid: No further relevant information available.

Incompatible materials: No further relevant information available.

Hazardous decomposition products: Carbon monoxide

11- TOXICOLOGICAL INFORMATION

Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:		
123-86-4 n-Butyl acetate		
Oral	LD50	13,100 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
1330-20-7 Xylene		
Oral	LD50	5,251 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	29 mg/l (rat)
7779-90-0 Trizinc bis(orthophosphate)		
Oral	LD50	>5,000 mg/kg (rat)
108-65-6 2-Methoxy-1-methylethyl acetate		
Oral	LD50	8,532 mg/kg (rat)
1100-41-4 Ethylbenzene		
Oral	LD50	3,500 mg/kg (rat)
Dermal	LD50	15,500 mg/kg (rabbit)
Inhalative	LC50/4 h	>24 mg/l (mouse)
112-07-2 2-Butoxyethyl acetate		
Oral	LD50	1,880 mg/kg (rat)
Dermal	LD50	1,480 mg/kg (rabbit)
1314-13-2 zinc oxide		
Oral	LD50	>5,000 mg/kg (rat)
7575-23-7 Pentaerythritol tetrakis(3-mercaptopropionate)		
Oral	LD50	1,000-2,000 mg/kg (rat)

Respiratory or skin sensitisation May cause an allergic skin reaction.

Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

12 – ECOLOGICAL INFORMATION

Toxicity

Aquatic toxicity: No further relevant information available.

Persistence and degradability: No further relevant information available.

Bioaccumulative potential: No further relevant information available.

Mobility in soil: No further relevant information available.

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

Endocrine disrupting properties: For information on endocrine disrupting properties see section 11.

Other adverse effects

Remark: Toxic for fish

Additional ecological information:

General notes:

Water hazard class 2 (German Regulation) : hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

13– DISPOSAL CONSIDERATION

Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Uncleaned packaging:

Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.






14– TRANSPORT INFORMATION

UN number or ID number

ADR, IMDG, IATA UN1263

UN proper shipping name

ADR UN1263 PAINT, ENVIRONMENTALLY HAZARDOUS
IMDG PAINT (Trizinc bis(orthophosphate), Polythiols), MARINE POLLUTANT

IATA	PAINT
Transport hazard class(es) ADR	
 	
Class Label	3 (F1) Flammable liquids. 3
IMDG	
 	
Class Label	3 Flammable liquids. 3
IATA	
	
Class Label	3 Flammable liquids. 3
Packing group ADR, IMDG, IATA	III
Environmental hazards:	Product contains environmentally hazardous substances:
Marine pollutant:	Dibutyltin dilaurate
Special marking (ADR):	Symbol (fish and tree)
Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	30
EMS Number:	F-E,S-E
Segregation groups	(SGG1) Acids
Stowage Category	A
Maritime transport in bulk according to IMO	

Instruments: Not applicable.

Transport/Additional information:

ADR

Limited quantities (LQ) 5L
Transport category 3
Tunnel restriction code D/E
Remarks: ≤ 5 l: 2.2.3.1.5 ADR

IMDG

Limited quantities (LQ) 5L
Remarks: ≤ 5 l: 2.3.2.5 IMDG

UN "Model Regulation": UN 1263 PAINT, 3, III, ENVIRONMENTALLY HAZARDOUS

15 – REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture.

Poisons Act

Regulated explosives precursors

None of the ingredients is listed.

Regulated poisons

None of the ingredients is listed.

Reportable explosives precursors

None of the ingredients is listed.

Reportable poisons

None of the ingredients is listed

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

National regulations:

Additional classification according to Decree on Hazardous Materials, Annex II:

Class	Share in %
I	<1
NK	25-50

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16-OTHER INFORMATION

Relevant phrases

H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H341 Suspected of causing genetic defects.
H360FD May damage fertility. May damage the unborn child.
H370 Causes damage to organs.
H372 Causes damage to organs through prolonged or repeated exposure.
H373 May cause damage to organs through prolonged or repeated exposure.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.
EUH066 Repeated exposure may cause skin dryness or cracking.

Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
DNEL: Derived No-Effect Level (UK REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative

- Flam. Liq. 2: Flammable liquids – Category 2
- Flam. Liq. 3: Flammable liquids – Category 3
- Acute Tox. 4: Acute toxicity – Category 4
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
- Skin Sens. 1: Skin sensitisation – Category 1
- Skin Sens. 1A: Skin sensitisation – Category 1A
- Muta. 2: Germ cell mutagenicity – Category 2
- Repr. 1B: Reproductive toxicity – Category 1B
- STOT SE 1: Specific target organ toxicity (single exposure) – Category 1
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
- STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
- Asp. Tox. 1: Aspiration hazard – Category 1
- Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
- Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
- Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
- Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

The information contained in these sheets is based on the present state of knowledge and current national legislation. It provides guidance on health, safety and environmental aspects and should not be construed as any guarantee of technical performance or suitability for particular applications.