

TECHNICAL DATA SHEET*Revision date: 30.07.2023***LEATHER PAINT**

Article number:	26801
Colour:	black
Intended use:	Car refinishing product/ Colour spray for smooth leather
General characteristics:	High quality leather spray to repair and embellish parts of leather, vinyl and artificial leather. <ul style="list-style-type: none">▪ Lasting colour and lasting gloss▪ Elastic▪ Excellent adhesion▪ Maintains the original structure
	Surfaces: vinyl, leather and artificial leather

Physical and chemical characteristics:

Basis of binder: nitrocellulose binder
Temperature resistance: to 50 °C
Size: aerosol cans, maximum nominal volume 400 ml
Gloss: satin matt
Coverage: 1-2 m²
VOC-content: approx..84% w/w
Solid content: approx..16% w/w

Application process:

Before use, carefully read and observe the warning texts on the label!

Pretreatment: the surface should be clean, dry and free of grease.

Treatment:

- The surface should be clean, dry and free of grease.
- The aerosol should have room temperature. Best processing temperature 15 to 25°C.
- Before use, shake the aerosol for 2 minutes and spray a sample.

- Distance to the surface to be treated approx.. 25 - 30 cm.
- Apply the vinyl spray in several thin layers.
- Before applying the next layer, again shake the aerosol.
- After use, clean the valve (turn aerosol upside down and press the nozzle for approx. 5 seconds).

The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.

Processing conditions:

Please only use in an adequate ventilated environment with an ample supply of fresh air. Processing temperature should be at least +10 °C and max. air humidity should not exceed 80%.

Drying	dust free	tack free	hardened/resprayable
Air drying 20 °C	5-10 min.	10-20 min.	after 2 h

Storage stability:

10 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)

This release replaces all eventually earlier issued versions.

For additional information, not contained in this technical data sheet, please contact the supplier under:

e-mail: info@chamaeleon-produktion.de

For safety information, please refer to the corresponding safety data sheet.