

SAFETY DATA SHEET
according to UK REACH

Revision date: 15.09.2025

1- IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/ UNDERTAKING**Product details****Trade name:** 2K to 1K Converter**Article number:** 13602**Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.

Intended use: Car refinishing Product/ Paint additive**Manufacturer/Supplier:**

Chamäleon GmbH

Rudolf-Diesel-Straße, 8a, 69115 Heidelberg

Germany

Further information obtainable from: Product Safety Department**Information in case of emergency:** + 49 70024112112 (CH)**2 – HAZARDS IDENTIFICATION****Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008**

GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

STOT RE 2 H373 May cause damage to the hearing organs through prolonged or repeated exposure.



GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage



GHS07

Skin Irrit. 2 H315 Causes skin irritation.
STOT SE 3 H336 May cause drowsiness or dizziness

Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



GHS02

GHS05

GHS07

GHS08

Signal word Danger

Hazard-determining components of labelling:

Butan-1-ol

n-Butyl acetate

Reaction mass of ethylbenzene and xylene

Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H336 May cause drowsiness or dizziness.

H373 May cause damage to the hearing organs through prolonged or repeated exposure.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P362+P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

3- COMPOSITION/INFORMATION ON INGREDIENTS

Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-Butyl acetate	50-100%
	Flam. Liq. 3, H226; STOT SE 3, H336, EUH066	
CAS: 9004-70-0	Nitrocellulose, nitrogen content <12,6%	10-25%
	Expl. 1.1, H201	
EC number: 905-588-0 Reg.nr.: 01-2119488216-32	Reaction mass of ethylbenzene and xylene	≥10-<25%
	Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335; Aquatic Chronic 3, H412	
CAS: 71-36-3 EINECS: 200-751-6 Reg.nr.: 01-2119484630-38	Butan-1-ol	≥3-<10%
	Flam. Liq. 3, H226; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336	
CAS: 112-07-2 EINECS: 203-933-3 Reg.nr.: 01-2119475112-47	2-Butoxyethyl acetate	5-<10%
	Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332	

Additional information: For the wording of the listed hazard phrases refer to section 16.

4- FIRST - AID MEASURE

Description of first aid measures

General information: Immediately remove any clothing soiled by the product.

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Immediately rinse with water.

After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing: If symptoms persist consult doctor.

Most important symptoms and effects, both acute and delayed No further relevant information available.

- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5- FIRE - FIGHTING MEASURE

Extinguishing media

Suitable extinguishing agents:

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents: Water with full jet

Special hazards arising from the substance or mixture:

During heating or in case of fire poisonous gases are produced.

Advice for firefighters

Protective equipment: Mouth respiratory protective device.

6- ACCIDENTAL RELEASE MEASURE

Personal precautions, protective equipment and emergency procedures:

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralising agent.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Reference to other sections:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7- HANDLING AND STORAGE

Precautions for safe handling:

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: No special requirements.

Information about storage in one common storage facility: Store away from foodstuffs.

Further information about storage conditions: Keep container tightly sealed.

Storage class: 3

Specific end use(s): No further relevant information available.

8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

Ingredients with limit values that require monitoring at the workplace:		
123-86-4 n-Butyl acetate		
WEL		Short-term value: 966 mg/m ³ , 200 ppm Long-term value: 724 mg/m ³ , 150 ppm
71-36-3 Butan-1-ol		
WEL		Short-term value: 154 mg/m ³ , 50 ppm Sk
112-07-2 2-Butoxyethyl acetate		
WEL		Short-term value: 332 mg/m ³ , 50 ppm Long-term value: 133 mg/m ³ , 20 ppm Sk
DNELs		
123-86-4 n-Butyl acetate		
Dermal	DNEL	6 mg/kg (general population) 11 mg/kg (Arbeiter)
Inhalative	DNEL	300 mg/m ³ (general population) 600 mg/m ³ (Arbeiter)
Reaction mass of ethylbenzene and xylene		
Dermal	DNEL	212 mg/kg (Arbeiter)
Inhalative	DNEL	221 mg/m ³ (Arbeiter)
112-07-2 2-Butoxyethyl acetate		
Dermal	DNEL	169 mg/kg (Arbeiter)
Inhalative	DNEL	133 mg/m ³ (Arbeiter)

Additional information: The lists valid during the making were used as basis.

Exposure controls

Appropriate engineering controls: No further data; see section 7.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the eyes.
Avoid contact with the eyes and skin.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Breakthrough time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection

Tightly sealed goggles

9 – PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

General Information

Physical state

Liquid

Colour:

According to product specification

Odour:

Characteristic

Odour threshold:

Not determined.

Melting point/freezing point:

Undetermined.

Boiling point or initial boiling point and boiling range:

116-118 °C (71-36-3 Butan-1-ol)

Flammability:

Flammable.

Lower and upper explosion limit

Lower:	1 Vol % (Reaction mass of ethylbenzene and xylene)
Upper:	8.5 Vol % (123-86-4 n-Butyl acetate)
Flash point:	28 °C (DIN 53213)
Auto-ignition temperature:	160 °C (DIN 51794, 9004-70-0 Nitrocellulose, nitrogen content <12,6%)
Decomposition temperature:	Not determined.
pH:	Not determined.
Viscosity:	
Kinematic viscosity at 20 °C	120 s (DIN 53211/4)
Dynamic:	Not determined.
Solubility	
water:	Not miscible or difficult to mix.
Partition coefficient n-octanol/water (log value):	Not determined.
Vapour pressure at 20 °C:	10.7 hPa (123-86-4 n-Butyl acetate)
Vapour pressure at 50 °C:	55 hPa
Density and/or relative density	
Density at 20 °C:	0.935 g/cm ³ (DIN 53217)
Relative density	Not determined.
Vapour density	Not determined.
Other information	
Appearance:	
Form:	Fluid
Important information on protection of health and environment, and on safety.	
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Solvent content:	
VOC (EC)	84.53 %
Solids content (weight-%):	15.5 %
Change in condition	
Evaporation rate:	Not determined.
Information with regard to physical hazard classes	
Explosives:	Void
Flammable gases:	Void
Aerosols:	Void
Oxidising gases:	Void
Gases under pressure:	Void
Flammable liquids:	Flammable liquid and vapour.
Flammable solids:	Void

Pyrophoric liquids:	Void
Pyrophoric solids:	Void
Self-reactive substances and mixtures:	Void
Self-heating substances and mixtures:	Void
Substances and mixtures, which emit flammable gases in contact with water:	Void
Oxidising liquids:	Void
Oxidising solids:	Void
Organic peroxides:	Void
Corrosive to metals:	Void
Desensitised explosives:	Void

10- STABILITY AND REACTIVITY

Reactivity No further relevant information available.

Chemical stability

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

Possibility of hazardous reactions: No dangerous reactions known.

Conditions to avoid: No further relevant information available.

Incompatible materials: No further relevant information available.

Hazardous decomposition products: Carbon monoxide

11- TOXICOLOGICAL INFORMATION

Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:		
123-86-4 n-Butyl acetate		
Oral	LD50	13,100 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Reaction mass of ethylbenzene and xylene		
Oral	LD50	3,500 mg/kg (rat)
Dermal	LD50	15,400 mg/kg (rat)
Inhalative	LC50/4 h	17.6 mg/l (rat)
71-36-3 Butan-1-ol		
Oral	LD50	2,290 mg/kg (rat)
Dermal	LD50	3,400 mg/kg (rabbit)
112-07-2 2-Butoxyethyl acetate		

Oral	LD50	1,880 mg/kg (rat)
Dermal	LD50	1,480 mg/kg (rabbit)

Primary irritant effect:

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/irritation Causes serious eye damage.

STOT-single exposure May cause drowsiness or dizziness.

STOT-repeated exposure May cause damage to the hearing organs through prolonged or repeated exposure.

Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

12 – ECOLOGICAL INFORMATION

Toxicity

Aquatic toxicity: No further relevant information available.

Persistence and degradability: No further relevant information available.

Bioaccumulative potential: No further relevant information available.

Mobility in soil: No further relevant information available.

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

Endocrine disrupting properties: The product does not contain substances with endocrine disrupting properties.

Other adverse effects

Additional ecological information:

General notes:

Water hazard class 2 (German Regulation) : hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Danger to drinking water if even small quantities leak into the ground.

13– DISPOSAL CONSIDERATION

Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

14- TRANSPORT INFORMATION

UN number or ID number

ADR, IMDG, IATA UN1263

UN proper shipping name

ADR UN1263 PAINT RELATED MATERIAL
IMDG, IATA PAINT RELATED MATERIAL

Transport hazard class(es)

ADR



Class 3 (F1) Flammable liquids.
Label 3

IMDG, IATA



Class 3 Flammable liquids.
Label 3

Packing group

ADR, IMDG, IATA III

Environmental hazards:

Marine pollutant: No

Special precautions for user Warning: Flammable liquids.

Hazard identification number (Kemler code): 30

EMS Number: F-E, S-E

Stowage Category A

Maritime transport in bulk according to IMO

Instruments: Not applicable.

Transport/Additional information:

ADR

Limited quantities (LQ) 5L

Transport category	3
Tunnel restriction code	D/E
Remarks:	≤ 450 l: 2.2.3.1.5 ADR
IMDG	
Limited quantities (LQ)	5L
Remarks:	≤ 450 l: 2.3.2.5 IMDG-Code
UN "Model Regulation":	UN 1263 PAINT RELATED MATERIAL, 3, III

1.5 – REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture.

Poisons Act

Regulated explosives precursors

None of the ingredients is listed.

Regulated poisons

None of the ingredients is listed.

Reportable explosives precursors

None of the ingredients is listed.

Reportable poisons

None of the ingredients is listed.

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category P5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

National regulations:

Additional classification according to Decree on Hazardous Materials, Annex II:

Class	Share in %
NK	50-100

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

1.6-OTHER INFORMATION

Relevant phrases

H201 Explosive; mass explosion hazard.

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H412 Harmful to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Expl. 1.1: Explosives – Division 1.1

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

The information contained in these sheets is based on the present state of knowledge and current national legislation. It provides guidance on health, safety and environmental aspects and should not be construed as any guarantee of technical performance or suitability for particular applications.