



CHAMÄLEON GMBH / RUDOLF-DIESEL-STRASSE 8A / 69115 HEIDELBERG / GERMANY

CHAMÄLEON GMBH
RUDOLF-DIESEL-STRASSE 8A
69115 HEIDELBERG
GERMANY

FON 0049 (0) 6221 - 520 440
FAX 0049 (0) 6221 - 520 449
MAIL INFO@CHAMAELEON-PRODUKTION.DE
WEB WWW.CHAMAELEON-PRODUKTION.DE

TECHNICAL DATA SHEET

Revision date: 10.06.2023

PRE-FILL STANDARD

Article number: 25001

Colour: depending on colour used

Intended use: Car refinishing product/ Preparation

General characteristics:

Chamäleon Pre-fill standard is a pre-filled can with propellant gases and solvent (275 ml) that can be filled with solvent-based basecoats (max. 100 ml). Ideal for spot repair or refinishing parts.

A spray can pre-filled with propellant and solvents. The paint is transferred via a filling device into the can to produce a ready-to-use end product (dealers liability)

- simple, time-saving application
- excellent atomisation
- light blending

Physical characteristics:

Smell: solvent

Efficiency: depending on consistence and colour of the ground

Substrate: depending on the colour of the substrate applicable on Primer filler, 2K Primer filler, 1K Epoxy primer, cured paint sanded

Drying time at 20°C, 50% relative air humidity: drying time depends on surrounding temperature, air humidity, thickness of the applied coat and the filled type of paint (refer to information of the paint manufacturer)

Size: aerosol cans, maximum nominal volume 400 ml, filling quantity 100ml

VOC-value: 218g

Processing conditions:

Please only use in an adequate ventilated environment with an ample supply of fresh air. Processing temperature should be at least +10 °C and max. air humidity should not exceed 80%.

Application process:

Before use, carefully read and observe the warning texts on the label!

- Clean the surface to be painted thoroughly with Chamäleon Silicone remover, then sand
- Larger bare surfaces must be pre-primed with the appropriate Chamäleon primer
- The area must be dry and free of dust and grease
- Shake the can vigorously for 2 minutes
- Carry out spray test
- Compatibility testing is necessary

For professional use only

Wear an appropriate respirator (recommended type A2/P3).

Storage stability:

Empty cans: 5 years.

Filled cans: depending on type of paint from several hours up to 6 months (information from a specialist dealer). If appropriate storage provided (=10°-25°C, relative air humidity max. 60%)

This release replaces all eventually earlier issued versions.

For additional information, not contained in this technical data sheet, please contact the supplier under:

e-mail: info@chamaeleon-produktion.de

For safety information, please refer to the corresponding safety data sheet.