

**SAFETY DATA SHEET**  
**according to 1907/2006/EC, Article 31**

Revision date: 16.03.2024

**1- IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/**  
**UNDERTAKING**

**Product details**

**Trade name:** Hardener for 455 Epoxy primer

**Article number:** 12554, 12557

**Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.

**Intended use:** Car refinishing Product/ Hardening agent/ Curing agent

**Manufacturer/Supplier:**

Chamäleon GmbH

Rudolf-Diesel-Straße, 8a, 69115 Heidelberg

Germany

**Further information obtainable from:** Product Safety Department

**Information in case of emergency:** + 49 70024112112 (CH)

**2 – HAZARDS IDENTIFICATION**

**Classification of the substance or mixture**

**Classification according to Regulation (EC) No 1272/2008**



flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



health hazard

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.  
Eye Dam. 1 H318 Causes serious eye damage



Skin Sens. 1 H317 May cause an allergic skin reaction.  
STOT SE 3 H335 May cause respiratory irritation.  
Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

#### Label elements

#### Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GP CLP regulation.

#### Hazard pictograms



GHS02

GHS05

GHS07

GHS08

#### Signal word Danger

#### Hazard-determining components of labelling:

Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine

Xylene

2,4,6-tris(dimethylaminomethyl)phenol

Polyaminoamide adduct

#### Hazard statements

H226 Flammable liquid and vapour.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

H373 May cause damage to the hearing organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

#### Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

- P103 Read carefully and follow all instructions.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P310 Immediately call a POISON CENTER/doctor.
- P321 Specific treatment (see on this label).
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- Other hazards**
- Results of PBT and vPvB assessment**
- PBT:** Not applicable.
- vPvB:** Not applicable.

### 3- COMPOSITION/INFORMATION ON INGREDIENTS

#### Mixtures

**Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	Xylene	50-100%
	Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	
CAS: 68082-29-1	Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	≥10-<25%
	Skin Corr. 1B, H314; Eye Dam. 1, H318; Aquatic Chronic 2, H411; Skin Sens. 1A, H317	
CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119489370-35	Ethylbenzene	≥10-<25%
	Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Aquatic Chronic 3, H412	
	Polyaminoamide adduct	2.5-<10%
	Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	
CAS: 90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	≥3-<5%

EINECS: 202-013-9 Reg.nr.: 01-2119560597-27	Skin Corr. 1C, H314; Eye Dam. 1, H318; Acute Tox. 4, H302	
CAS: 90640-67-8 EINECS: 292-588-2 Reg.nr.: 01-2119487919-13	Amines, polyethylenepoly-, triethylenetetramine fraction Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥0.1-<1%

#### Additional information:

For the wording of the listed hazard phrases refer to section 16.

### 4- FIRST - AID MEASURE

#### Description of first aid measures

**General information:** Immediately remove any clothing soiled by the product.

#### After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

**After skin contact:** Immediately rinse with water.

#### After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

**After swallowing:** If symptoms persist consult doctor.

**Most important symptoms and effects, both acute and delayed** No further relevant information available.

#### Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### 5- FIRE - FIGHTING MEASURE

#### Extinguishing media

#### Suitable extinguishing agents:

CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

**For safety reasons unsuitable extinguishing agents:** Water with full jet

#### Special hazards arising from the substance or mixture:

During heating or in case of fire poisonous gases are produced.

#### Advice for firefighters

**Protective equipment:** Mouth respiratory protective device.

## **6- ACCIDENTAL RELEASE MEASURE**

### **Personal precautions, protective equipment and emergency procedures:**

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

### **Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

### **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralising agent.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

### **Reference to other sections:**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## **7- HANDLING AND STORAGE**

### **Precautions for safe handling:**

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

### **Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

### **Conditions for safe storage, including any incompatibilities**

#### **Storage:**

**Requirements to be met by storerooms and receptacles:** No special requirements.

**Information about storage in one common storage facility:** Store away from foodstuffs.

**Further information about storage conditions:** Keep container tightly sealed.

**Storage class:** 3

**Specific end use(s):** No further relevant information available.

## 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

### Control parameters

Ingredients with limit values that require monitoring at the workplace:	
1330-20-7 Xylene	
WEL	Short-term value: 441 mg/m <sup>3</sup> , 100 ppm Long-term value: 220 mg/m <sup>3</sup> , 50 ppm Sk; BMGV
100-41-4 Ethylbenzene	
WEL	Short-term value: 552 mg/m <sup>3</sup> , 125 ppm Long-term value: 441 mg/m <sup>3</sup> , 100 ppm Sk
Ingredients with biological limit values:	
1330-20-7 Xylene	
BMGV	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid

**Additional information:** The lists valid during the making were used as basis.

### Exposure controls

**Appropriate engineering controls:** No further data; see section 7.

### Individual protection measures, such as personal protective equipment

#### General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

#### Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

#### Protection of hands:

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

#### Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of

- the glove material can not be calculated in advance and has therefore to be checked prior to the application.

### Eye/face protection

Tightly sealed goggles

## 9 – PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

#### General Information

Physical state

Fluid

Colour:

According to product specification

Odour:

Characteristic

Odour threshold:

Not determined.

Melting point/freezing point:

Undetermined.

Boiling point or initial boiling point and  
boiling range:

136 °C (100-41-4 Ethylbenzene)

Flammability:

Flammable.

Lower and upper explosion limit

Lower:

1 Vol % (100-41-4 Ethylbenzene)

Upper:

7.8 Vol % (100-41-4 Ethylbenzene)

Flash point:

24 °C (DIN EN ISO 1523:2002)

Auto-ignition temperature:

430 °C (DIN 51794, 100-41-4 Ethylbenzene)

Decomposition temperature:

Not determined.

pH:

Not determined.

Viscosity:

Kinematic viscosity at 20 °C:

20 s (DIN 53211/4)

Dynamic:

Not determined

Solubility

water:

Not miscible or difficult to mix.

Partition coefficient n-octanol/water (log value):

Not determined.

Vapour pressure at 20 °C:

9.5 hPa (100-41-4 Ethylbenzene)

Density and/or relative density

Density at 20 °C:

0.896 g/cm<sup>3</sup> (DIN EN ISO 2811-1)

Relative density

Not determined.

Vapour density

Not determined.

#### Other information

Appearance:

Form:

Fluid

Important information on protection of health and  
environment, and on safety.

<b>Ignition temperature:</b>	Product is not selfigniting.
<b>Explosive properties:</b>	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
<b>Solvent content:</b>	
<b>VOC (EC)</b>	73.00 %
<b>Solids content (weight-%):</b>	27.0 %
<b>Change in condition</b>	
<b>Evaporation rate:</b>	Not determined.
<b>Information with regard to physical hazard classes</b>	
<b>Explosives:</b>	Void
<b>Flammable gases:</b>	Void
<b>Aerosols:</b>	Void
<b>Oxidising gases:</b>	Void
<b>Gases under pressure:</b>	Void
<b>Flammable liquids:</b>	Flammable liquid and vapour.
<b>Flammable solids:</b>	Void
<b>Self-reactive substances and mixtures:</b>	Void
<b>Pyrophoric liquids:</b>	Void
<b>Pyrophoric solids:</b>	Void
<b>Self-heating substances and mixtures:</b>	Void
<b>Substances and mixtures, which emit flammable gases in contact with water:</b>	Void
<b>Oxidising liquids:</b>	Void
<b>Oxidising solids:</b>	Void
<b>Organic peroxides:</b>	Void
<b>Corrosive to metals</b>	Void
<b>Desensitised explosives</b>	Void

## 10- STABILITY AND REACTIVITY

**Reactivity** No further relevant information available.

**Chemical stability**

**Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

**Possibility of hazardous reactions:** No dangerous reactions known.

**Conditions to avoid:** No further relevant information available.

**Incompatible materials:** No further relevant information available.

**Hazardous decomposition products:** Carbon monoxide



## 11 – TOXICOLOGICAL INFORMATION

Information on hazard classes as defined in Regulation (EC) No 1272/2008

**Acute toxicity** Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:		
1330-20-7 Xylene		
Oral	LD50	5,251 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	29 mg/l (rat)

**Skin corrosion/irritation** Causes severe skin burns and eye damage.

**Serious eye damage/irritation** Causes serious eye damage.

**Respiratory or skin sensitisation** May cause an allergic skin reaction.

**STOT-single exposure** May cause respiratory irritation.

**STOT-repeated exposure** May cause damage to the hearing organs through prolonged or repeated exposure.

**Information on other hazards**

**Endocrine disrupting properties** None of the ingredients is listed.

## 12 – ECOLOGICAL INFORMATION

**Toxicity**

**Aquatic toxicity:** No further relevant information available.

**Persistence and degradability:** No further relevant information available.

**Bioaccumulative potential:** No further relevant information available.

**Mobility in soil:** No further relevant information available.

**Results of PBT and vPvB assessment**

PBT: Not applicable.

vPvB: Not applicable.

**Endocrine disrupting properties:**

The product does not contain substances with endocrine disrupting properties.

**Other adverse effects**

**Remark:** Harmful to fish

**Additional ecological information:**

**General notes:**

Water hazard class 2 (German Regulation) : hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

### 13- DISPOSAL CONSIDERATION

#### Waste treatment methods

##### Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

##### Uncleaned packaging:

**Recommendation:** Disposal must be made according to official regulations.

### 14- TRANSPORT INFORMATION

#### UN number or ID number

ADR, IMDG, IATA UN3470

#### UN proper shipping name

ADR UN3470 PAINT RELATED MATERIAL, CORROSIVE,  
FLAMMABLE  
IMDG, IATA PAINT RELATED MATERIAL, CORROS IVE,  
FLAMMABLE

#### Transport hazard class(es)

ADR



Class 8 (CF1) Corrosive substances.  
Label 8+3

IMDG



Class 8 Corrosive substances.  
Label 8/3

CHAMÄLEON GMBH / RUDOLF-DIESEL-STRASSE 8A / 69115 HEIDELBERG / GERMANY

CHAMÄLEON GMBH  
RUDOLF-DIESEL-STRASSE 8A  
69115 HEIDELBERG  
GERMANY

FON 0049 (0) 6221 - 520 440  
FAX 0049 (0) 6221 - 520 449  
MAIL [INFO@CHAMAELEON-PRODUKTION.DE](mailto:INFO@CHAMAELEON-PRODUKTION.DE)  
WEB [WWW.CHAMAELEON-PRODUKTION.DE](http://WWW.CHAMAELEON-PRODUKTION.DE)

## IATA



**Class** 8 Corrosive substances.  
**Label** 8 (3)

**Packing group**  
ADR, IMDG, IATA III

### Environmental hazards:

Marine pollutant: No  
Special precautions for user Warning: Corrosive substances.  
Hazard identification number (Kemler code): 83  
EMS Number: F-E,S-C  
Stowage Category B  
Stowage Code SW2 Clear of living quarters.

### Maritime transport in bulk according to IMO

**Instruments:** Not applicable.

### Transport/Additional information:

ADR  
Limited quantities (LQ) 1L  
Transport category 2  
Tunnel restriction code D/E

IMDG  
Limited quantities (LQ) 1L

UN "Model Regulation": UN 3470 PAINT RELATED MATERIAL, CORROSIVE, FLAMMABLE, 8 (3), II

## 15 – REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture.  
Poisons Act

- **Regulated explosives precursors**  
None of the ingredients is listed.
  - Regulated poisons**  
None of the ingredients is listed.
  - Reportable explosives precursors**  
None of the ingredients is listed.
  - Reportable poisons**  
None of the ingredients is listed.
  - Directive 2012/18/EU**  
**Named dangerous substances - ANNEX I** None of the ingredients is listed.
  - Seveso category P5c FLAMMABLE LIQUIDS**
  - Qualifying quantity (tonnes) for the application of lower-tier requirements** 5000 t
  - Qualifying quantity (tonnes) for the application of upper-tier requirements** 50000 t
  - National regulations:**  
**Additional classification according to Decree on Hazardous Materials, Annex II:**
- | Class | Share in % |
|-------|------------|
| NK    | 50-100     |
- Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16-OTHER INFORMATION

### Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.

### Classification according to Regulation (EC) No 1272/2008

- The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

**Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Corr. 1C: Skin corrosion/irritation – Category 1C

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1A: Skin sensitisation – Category 1A

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

The information contained in these sheets is based on the present state of knowledge and current national legislation. It provides guidance on health, safety and environmental aspects and should not be construed as any guarantee of technical performance or suitability for particular applications.