



CHAMÄLEON GMBH RUDOLF-DIESEL-STRASSE 8A 69115 HEIDELBERG GERMANY

 FON
 0049 (0) 6221 - 520 440

 FAX
 0049 (0) 6221 - 520 449

 Mall
 INFO@CHAMAELEON-PRODUKTION.DE

 WEB
 WWW.CHAMAELEON-PRODUKTION.DE

CHAMALEO

TECHNICAL DATA SHEET

POLISHING PAD – VERY HARD (WHITE)

Article number:

Intended use:

General characteristics:

Car refinishing product/ Polishing, griding

49120, 49220, 49320

- for mechanical polishing and griding;
- suited for using with coarse-grained polishing pastes.

Product characteristics:

- structure of the foam allow to hold the water inside the pad, what decrease the temperature of the polishing surface;
- the pad does not get into vibration during the work, which has a considerble effect on its life time;
- the Velcro holder is made from very strong, reusable material. It allows the pad to be securaly fitted into the polisher;
- the plastic holder is topped with the nut what easily and permanently allow to install and uninstall the pad on the polisher/sander;
- color: White

Available types of working surface:

flat

Technical characteristics:

- the plastic holder is manufactured of hard poli(akrylonitryl-co-butadien-co-styren) (ABS) plastic,
- the Velcro holder hook-up type
- the foam is polyurethane, polyester type, high resistantce and shock absorption
- genera physical parameters of foam:

FEATURES	UNIT	VALUE
Density	kg/m3	36 – 41
Rigidity 40%	kPa	6.5 – 9.5





CHAMÄLEON GMBH / RUDOLF-DIESEL-STRASSE 8A / 69115 HEIDELBERG / GERMANY

CHAMÄLEON GMBH RUDOLF-DIESEL-STRASSE 8A 69115 HEIDELBERG GERMANY

 FON
 0049 (0) 6221 - 520 440

 FAX
 0049 (0) 6221 - 520 449

 MAIL
 INFO@CHAMAELEON-PRODUKTION.DE

 WEB
 WWW.CHAMAELEON-PRODUKTION.DE

Elongation at break	%	90
Tensile strenght	kPa	190
Cell diameter	Mikron	500 - 700
Tear resistance	N/cm	7

Usage:

the pad can be applied both wet and dry at maximum rotation speed 2600 rpm without load.

Available sizes:

150mm x 50mm 150mm x 25mm

Available holders:

plastic thread M14 Velcro

This release replaces all eventually earlier issued versions.

For additional information, not contained in this Technical Data Sheet, please contact the supplier via: info@chamaeleon-produktion.de For safety information, please refer to the corresponding Safety Data Sheet.